



**Type G**  
Dished Top,  
Flat Base



**Type D**  
Dished Top and  
Bottom, Mounted on Skirt



**Type D**  
Dished Top and  
Bottom, Mounted on Legs

Manufactured in accordance with BS 799: Part 5: Type 'D' or 'G'.

All welded seams, Certified tested.

Fitted with 600mm dia. manhole with set pinned cover and gasket.

Standard connections include two 65mm, one 40mm and one 25mm screwed sockets.

Finished one coat of primer/gloss finish. or to customer's requirements.

### Dimensions and Capacities

Cat No.	Nom. Capacity	Overall Height	Internal Diameter	Shell Thick.	Base Thick	Approx Weight kg
	litres	meters	metres	mm	mm	
V01	2273	1.75	1.37	6	6	460
V02	2841	2.06	1.37	6	6	530
V03	3409	2.44	1.37	6	6	630
V04	4546	3.28	1.37	6	6	790
V05	5682	3.36	1.52	6	6	960
V06	6819	2.82	1.83	6	6	1050
V07	7955	3.36	1.83	6	6	1170
V08	9092	3.28	1.98	6	6	1230
V09	9092	3.73	1.83	6	6	1260
V10	11365	3.96	1.98	6	6	1480
V11	11365	4.65	1.83	6	6	1510
V12	13638	4.12	2.13	6	8	1620
V13	13638	4.80	1.98	6	6	1750
V14	13638	5.56	1.83	6	6	1780
V15	18184	4.72	2.29	6	8	1970
V16	22730	5.96	2.29	6	8	2400
V17	22730	5.10	2.44	6	8	2370
V19	27275	5.03	2.74	6	10	2690
V20	27275	6.17	2.44	6	8	2780
V21	31821	5.79	2.74	6	10	2860
V22	36367	6.45	2.74	6	10	3350
V23	40913	7.31	2.74	6	10	3690
V24	45459	8.05	2.74	6	10	3950
V25	54551	9.75	2.74	6	10	4720
V26	68189	10.26	3.00	6	10	5430
V27	90918	13.65	3.00	6	10	6850
V28	100010	14.93	3.00	6	10	7044
V29	113647	16.93	3.00	6	10	7924
V30	136377	11.73	4.00	8	10	11500